AS-R BAS **Cold Room Trailer Unit**

Technical data

Characteristics	м.u.	Value
Working temperature	°C	-15 ÷ -25
Starting mode		Direct
Voltage	Volt-Ph-Hz	240/1~/50
Rated input	kW*	1,07
Rated input	Amp*	6,18
Peak current	Amp	33,8
Max current	Amp	8,4
Refrigerant		R404A
	GWP	3922
Defrost		Hot gas
Mass	Kg	65
Compressor		
Туре		Hermetic
Nominal power	ĸW	1,3
Condenser		
Air flow	m³/h	700
Evaporator		
Air flow	m³/h	600
Air throw	m**	4
PED Category		0

Part no. BAS123TR02F





Power data

V120 V100 V80 m ³ m ³ m ³	Ta P P PC watt Kcal/h	Calculation of the refrigerating power	
15 13 12	20 1698 1460	and volume	
13 12 10	25 1568 1348	Та	
12 11 9,4	30 1437 1236	40,0 °C	
9,9 8,8 7,7	35 1305 1122	Tc	
8,3 7,4 6,5	40 1171 1007		
6,7 6 5,2	45 1037 892	-20,0 °C	
13 12 10	20 1532 1318	PF	
11 9,8 8,6	25 1405 1208		
9,6 8,5 7,5	30 1277 1098	1.016 Watt	
8 7,1 6,2	35 1147 986	874 Kcal/ł	
6,5 5,8 5,1	40 1016 874	V120	
5,1 4,5 4	45 884 760		
11 9,8 8,6	20 1367 1176	6,5 m ³	
9,1 8,1 7,1	25 1242 1068	V100	
7,6 6,8 5,9	30 1116 960	5,8 m³	
6,2 5,5 4,8	35 989 851	V80	
4,9 4,4 3,8	40 861 740		
3,7 3,3 2,9	45 731 629	5,1 m ³	

Та	
40,0	°C
Тс	
-20,0	°C
PF	
1.016	Watt
874	Kcal/h
V120	
6,5	m³
V100	
5,8	m ³
V80	
5,1	m ³

* When normally running: -20 \div +30°C ** Use air throw as a base. Air throw is affected by many factors such as height of room, product storage, location of evaporator, etc. Tc: Coldroom temp. - Ta: External temp.

P: Refrigerant capacity - V: Recommended cold-room volume

Auto Frigo offers Zanotti AS-R refrigeration units specifically designed for transportable Cold Room trailers.

AS-R Cold Room units are built to be extremely durable in all weather conditions with all the hardware cased in tough ABS plastic, which also protects the condenser unit from UV damage from prolonged exposure in the sun.


They are designed to be a stationary Cold Room trailer unit, operating via 240v power port. Suitable for mobile offices, functions and events. They can be plugged into a wall socket or connected to a petrol powered generator.

Learn more about AS-R BAS and MAS Cold Room Refrigeration units at https://www.autofrigo.com.au/asr-coldroomtrailer-units/






AS-R123



Schema di montaggio - Mounting scheme - Schema de montage Montageschema - Esquema de montaje






* Raccomandazioni in sede di installazione e per il controllo fornite sul manuale di installazione

To be advised at time of order for factory installation and operating instructions

Recommandations au moments d'installations et pour le contrôle fournis sur le manuel d'installation

- * Empfehlungen für die Installationsphase und zur Kontrolle, die im Handbuch zur Installation enthalten sind
- * Por cuanto respecta a recomendaciones de instalación y control ver manual de instalación

Massa e misure imballi - Packing mass and dimensions - Masse et dimensions emballages Verpackungsmasse und-abmessungen - Masa y medidas del embalaje



ZANOTTI S.p.A.

Terms & Conditions apply. Go to https://www.autofrigo.com.au/terms-conditions/

2019 AUTO FRIGO Via 70 Austrak Drive, Somerton 3062 (VIC) - Australia | Telephone: +61 39308 9977, AH: 13000 FRIGO | www.autofrigo.com.au